



THERMOCOUPLE ORDERING CODE

LG1	-	1	-	2	-	3	4	5	-	6
LG2	-	1	-	2	-	3	4	5	-	6
LG3	-	1	-	2	-	3	4	5	-	6
LG4	-	1	-	2	-	3	4	5	-	6

Example 1, LG Model, LG1, Type K, Lug Size : M4, Wire Length : 2 mtr, Wire Type : Fiberglass/Fiberglass, Class 2.
Order Code : LG1-K-M4-2FGCL2-0

Example 2, LG Model, LG2, Type K, Lug Size : M4, Wire Length : 2 mtr, Wire Type : Fiberglass/Fiberglass, Class 2.
Order Code : LG2-K-M4-2FGCL2-0

Example 3, LG Model, LG3, Type K, Lug Size : M4, Wire Length : 2 mtr, Wire Type : Fiberglass/Fiberglass/StainlessSteel Braided, Class 2.
Order Code : LG3-KM4-2FGSCL2-0

Example 4, LG Model, LG4, Type K, Lug Size : M4, Wire Length : 2 mtr, Wire Type : Fiberglass/Fiberglass/StainlessSteel Braided, Class 2.
Order Code : LG4-K-M4-2FGSCL2-0

1 CALIBRATION

Single

K: K E: E
J: J T: T

2 LUG SIZE

(Specify ring cable lug size accordingly)

M3 : M3

M4 : M4

3 WIRE LENGTH

1: 1 Meter

2: 2 Meter

3: 3 Meter

4 WIRE TYPE

FGS : Fiberglass/Fiberglass/Stainless Steel Braid – Solid Core

FGST : Fiberglass/Fiberglass/Stainless Steel Braid - Stranded

FG : Fiberglass/Fiberglass

T : MFA/MFA

5 TOLERANCE

CL2 : Class 2 (Standard industrial class)

6 CONNECTORS (OPTIONAL ITEM)

0 : Nil

CN1 : Miniature connector

CN1WC : Miniature connector + wire clamp

CNS1 : Standard connector

CNS1WC : Standard connector + wire clamp

CNS1 : Standard connector

Remarks: Not all combination are available however we will offer the nearest to your requirement